

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME I LIGHT LIST, 2001							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
3302	Penobscot Bay Lighted Buoy WP		MO (A)		4	Red and white with red spherical topmark.	
	*		*		*	*	17/02
	Pine Orchard Harbor						
23946	Breakwater Light	41 15 48 N 72 46 18 W				SG on pile.	Private aid.
	*					*	* 17/02
23946.1	- Buoy 1	41 15 48 N 72 46 18 W				Green can.	Maintained from Apr. 1 to Nov. 1. Private aid.
	*	*				*	17/02
	*Add Heading: *Westchester Creek						
*23946.2	- Buoy 2					Red nun.	
							17/02
	*Add Headings: *Duck Island Roads *Pine Orchard Harbor						
23946.5	- Buoy 3					Green can.	Maintained from Apr. 1 to Nov. 1. Private aid.
							17/02
CORRECTIONS TO C. G. LIGHT LIST, VOLUME II LIGHT LIST, 2002							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
*595	NOAA Lighted Buoy 44DUK	36 11 17 N 75 44 07 W	FI (4) Y 20s			Yellow discshaped.	Maintained by NOAA.
							17/02
1440	- EAST JETTY LIGHT 4		FI R 4s	25	6	TR on skeleton tower.	
				*			17/02
1445	- WEST JETTY LIGHT 5	38 56 12 N 74 51 55 W	FI G 4s	20	6	SG on pile.	
		*			*	*	17/02
1695	EAST POINT LIGHT	39 11 45 N 75 01 38 W	Iso W 6s (R sector)	43	W R 9 7	On pile on masonry structure.	Red sector from 055° to 017°.
		*					17/02
	Cohansey						
1990	- LIGHT	39 20 30 N 75 21 41 W	FI W 4s (2 R sectors)	42	W R 8 6	NB on black skeleton tower.	Red from 068° to 098° and from 275° to 305°.
					*		17/02

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME II LIGHT LIST, 2002							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
2050	- NORTH END LIGHT	38 49 57 N 75 06 21 W	FI G 4s	40	6	SG on skeleton tower.	
		*					17/02
2097	- LIGHT 2		FI R 4s	15	3	TR on pile.	
					*		17/02
Salem River Entrance							
2645	- Lighted Buoy 2	39 32 40 N 75 32 14 W	FI R 4s		4	Red.	Replaced by LIB of lower intensity from Jan. 1 to Feb. 28.
		*					17/02
8895	- Lighted Buoy 47		FI G 4s		5	Green.	Replaced by LIB of lower intensity from the first Tuesday after Thanksgiving to Mar. 15.
					*		17/02
8900	- Lighted Buoy 48		FI R 4s		5	Red.	Replaced by LIB of lower intensity from the first Tuesday after Thanksgiving to Mar. 15.
					*		17/02
8905	- Lighted Buoy 49		FI G 6s		6	Green.	Replaced by LIB of lower intensity from the first Tuesday after Thanksgiving to Mar. 15.
					*		17/02
8920	- Lighted Buoy 50		FI R 6s		5	Red.	Replaced by LIB of lower intensity from the first Tuesday after Thanksgiving to Mar. 15.
					*		17/02
CAPE CHARLES TO WOLF TRAP (Chart 12224)							
21430	CHERRYSTONE CHANNEL LIGHT 2	37 12 02 N 76 01 32 W	FI R 2.5s	18	4	TR on pile.	Light equipment removed when endangered by ice.
		*					* 17/02
CORRECTIONS TO C. G. LIGHT LIST, VOLUME III LIGHT LIST, 2001							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
2625 34580	- SOUTH CHANNEL RANGE FRONT LIGHT	32 45 32 N 79 55 37 W	Q G	13		KRW-I on dolphin.	Visible all around; higher intensity on rangeline.
		*					17/02
2630 34585	- SOUTH CHANNEL RANGE REAR LIGHT 633 yards, 269.1° from front light.		Iso G 6s	42		KRW on skeleton tower on piles.	Visible 2° each side of rangeline.
	*						17/02

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME III LIGHT LIST, 2001							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
34580 2625	- SOUTH CHANNEL RANGE FRONT LIGHT	32 45 32 N 79 55 37 W	Q G	13		KRW-I on dolphin.	Visible all around; higher intensity on rangeline.
		*					17/02
34585 2630	- SOUTH CHANNEL RANGE REAR LIGHT 633 yards, 269.1° from front light.		Iso G 6s	42		KRW on skeleton tower on piles.	Visible 2° each side of rangeline.
	*						17/02
CORRECTIONS TO C. G. LIGHT LIST, VOLUME IV LIGHT LIST, 2001							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
3085	- RANGE FRONT LIGHT						<i>Remove from list.</i>
							* 17/02
3090	- RANGE REAR LIGHT 135 yards, 113° from front light.						<i>Remove from list.</i>
							* 17/02
4045	FORT McREE LEADING LIGHT	30 19 32 N 87 18 47 W	Q W	32	5	NB on skeleton tower.	Higher intensity beam up channel.
		*					17/02
CORRECTIONS TO C. G. LIGHT LIST, VOLUME VI LIGHT LIST, 2001							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
SAN FRANCISCO TO POINT ARENA (Chart 18640)							
382	NOAA Environmental Lighted Buoy 46059	38 02 00 N 129 56 00 W	FI (4) Y 20s			Yellow boat-shaped buoy.	
		*					17/02
Vancouver							
11215	- DIRECTION LIGHT	45 39 27 N 122 46 01 W	Iso W 6s (G & R sectors)	50		On same pile structure with skeleton tower as Morgan Channel Light 42.	Centerline bearing 307.5°. White visible 1° each side of centerline. Green visible from 304.5° to 306.5°. Red visible from 308.5° to 310.1°.
							* 17/02
*Delete Headings: *MCNARY DAM TO JUNIPER (Chart 18541) *Lake Wallula *McNary Boat Ramp							
12775	- Buoy 1						<i>Remove from list.</i>
							* 17/02

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME VI LIGHT LIST, 2001

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
*Change Headings to Read: *MCNARY DAM TO JUNIPER (Chart 18541) *Winthrop Channel							
*12776	Lake Wallula Pump station Danger Lighted Buoy A	45 55 24 N 119 07 15 W	FI Y 2s		Yellow		Private aid. 17/02
*Delete Headings: *Lake Wallula *McNary Boat Ramp							
12780	- Buoy 2						Remove from list. * 17/02
12785	- Buoy 3						Remove from list. * 17/02
12790	- Buoy 4						Remove from list. * 17/02
12795	- Buoy 5						Remove from list. * 17/02
12800	- Buoy 6						Remove from list. * 17/02
12805	- Buoy 7						Remove from list. * 17/02
12810	- Buoy 8						Remove from list. * 17/02
*Add Headings: *Lake Wallula *McNary Boat Ramp							
12815	Lake Wallula Lighted Buoy 2	45 56 28 N 119 17 15 W	FI R 4s		4 Red.		17/02

CORRECTIONS TO C. G. LIGHT LIST, VOLUME VII LIGHT LIST, 2002

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
3955	EASTLAKE INTAKE BREAKWATER LIGHT	41 40 27 N 81 26 50 W	Q Y	18 5		NW on post worded DANGER.	Maintained from Apr. 15 to Dec. 1. Private aid. 17/02
*							
4160	- Main Entrance Light	41 30 32 N 81 43 04 W	AI WR 10s 0.1s W fl 4.9s ec. 0.1s R fl 4.9s ec.	63 19	W 16	White conical tower with fog signal building attached.	Tower floodlighted from sunset to sunrise. HORN: 2 blasts ev 30s (2s bl-2s si-2s bl-24s si). Operates from Apr. 1 to Dec. 1. * 17/02

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME VII LIGHT LIST, 2002							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
LORAIN HARBOR (Chart 14841)							
Lorain Harbor							
4320	- LIGHT	41 28 54 N 82 11 42 W	FI W 6s	60 18	16	On tower.	HORN: 1 blast ev 30s (3s bl). Operates from Apr. 15 to Nov. 15. * 17/02
5255	PLEASANT POINTE NORTH PIER LIGHT	41 32 24 N 82 42 54 W	F W	16 5	On post.		Maintained from Apr. 15 to Nov. 30. Private aid. * 17/02
5849.3	LEMARIN ENTRANCE LIGHT 5	41 33 33 N 82 51 10 W	F G	20 6	SG on concrete pile.		Maintained from Apr. 1 to Nov. 30. Private aid. * 17/02
5849.4	LEMARIN ENTRANCE LIGHT 6	41 33 32 N 82 51 11 W	F R	20 6	TR on concrete pile.		Maintained from Apr. 1 to Nov. 30. Private aid. * 17/02
5861	<i>Port Clinton Regional Water Intake Crib Lighted Buoy</i>	41 31 21 N 82 56 19 W	FI W 4s			White with orange bands and diamond worded DANGER CRIB.	Maintained from May 15 to Oct. 15. Private aid. * 17/02
6040	- <i>Safe Water Lighted Buoy</i>	41 50 08 N 83 10 11 W	Mo (A) W		7	Red and white stripes.	 * 17/02
6240	- Buoy 40	41 42 42 N 83 26 02 W				Red nun.	 * 17/02
6570	- <i>Lighted Buoy 1</i>	41 52 31 N 83 16 52 W	FI G 2.5s		4	Green.	Replaced by can from Dec. 14 to Apr. 14. * 17/02
6835	- Light (C)	41 51 12 N 82 34 54 W	FI W 4s	91 28	10	White circular tower with green upper and lower portions; on pier. 80	RACON: M (--) Winter light FI W 4s. Seasonal. * 17/02
7065	- LIGHT 51D (C)						<i>Remove from list.</i> * 17/02
St. Clair Cut-Off Channel							
8590	- <i>Preferred Channel Lighted Buoy</i>	42 31 00 N 82 41 24 W	FI (2+1) G 6s		4	Green and red bands.	Replaced by can from Dec. 21 to Mar. 28.. * 17/02

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME VII LIGHT LIST, 2002

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
Lake Huron Cut							
<i>Lighted buoys maintained from Apr. 1 to Dec. 21 unless otherwise noted.</i>							
10035	- Lighted Buoy 1		Q G		4	Green.	Replaced by LIB of reduced intensity from Dec. 21 to Apr. 1. * 17/02
10790	- Lighted Buoy 7		FI G 4s		4	Green.	Can; winter marker. * 17/02
10800	- Lighted Buoy 10		FI R 4s		4	Red.	Nun; winter marker. * 17/02
10860	- Lighted Buoy 31		FI G 4s		4	Green.	Can; winter marker. * 17/02
10865	- Lighted Buoy 35		FI G 4s		4	Green.	Can; winter marker. * 17/02
10875	- Lighted Buoy 36		FI R 4s		4	Red.	Nun; winter marker. * 17/02
10900	- Lighted Buoy 43		FI G 2.5s		4	Green.	Can; winter marker. * 17/02
10910	- Lighted Buoy 45		FI G 4s		4	Green.	Can; winter marker. * 17/02
10990	- Lighted Buoy 62		FI R 4s		4	Red.	Nun; winter marker. * 17/02
11045	- Lighted Buoy 71		FI G 4s		4	Green.	Can; winter marker. * 17/02
11170	ALABASTER TRAMWAY RANGE REAR LIGHT 170 feet, 270° from light.		F R	70 21		Gray box.	Private aid. * 17/02
14015	FRECHETTE POINT RANGE FRONT LIGHT	46 27 18 N 84 16 42 W	Q G	30 9		KRW on square skeleton tower.	Visible on range line only. * 17/02
14020	FRECHETTE POINT RANGE REAR LIGHT 4,483 feet, 323.3° from front light.		F G	90 27		KRW on triangular skeleton tower.	Visible on range line only. * 17/02

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME VII LIGHT LIST, 2002							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
14191	GEORGE KEMP MARINA EAST LIGHT	46 30 01 N 84 20 11 W	FI G 4s	12 4		On tower.	Maintained from May 1 to Oct. 31. Private aid.
						*	17/02
14192	GEORGE KEMP MARINA WEST LIGHT	46 30 02 N 84 20 14 W	FI R 4s	12 4		On piling with tower.	Maintained from May 1 to Oct. 31. Private aid.
						*	17/02
15155	<i>Keweenaw Point Lighted Buoy 1</i>		FI G 4s		4	Green.	Maintained from May 14 to Oct. 14.
							* 17/02
16200	- RANGE REAR LIGHT 1,020 feet, 084.5° from front light.		F G	39 12		KRW on white cylindrical tower.	
						*	17/02
16770	<i>Middle Island Passage Lighted Bell Buoy 2</i>	48 05 27 N 88 34 20 W	FI R 4s		4	Red.	Maintained from Oct. 14 to May 28.
							* 17/02
16855	Michipicoten Harbor Light (C)	47 56 36 N 84 54 24 W	FI W 30s	88 27	18	Skeleton tower. 40	Seasonal. HORN: 2 blasts ev 60s (3s bl). Horn points 210°. Operates by keying mike 5 times on VHF-FM Ch. 19. Emergency light.
							* 17/02
18395	- SOUTH PIERHEAD LIGHT		F R 6s	30 9	6	TR on post.	
			*				17/02
19675	- East Breakwater Light	41 40 51 N 87 26 28 W	Iso G 6s	78 24	20	Square tower. 75	HORN: 2 blasts ev 20s (2s bl-2s si-2s bl-14s si). Operates from Apr. to Dec.
		*					17/02
19800	- Harbor Breakwater South End Light	41 43 34 N 87 29 36 W	AI WR 10s 0.2s W fl 4.8s ec. 0.2s R fl 4.8s ec.	50 15	W 17 R 14	White square skeleton tower with red band. Lower half open.	HORN: 1 blast ev 15s (2s bl). Operates from Apr. to Dec.
		*					17/02
Kenosha							
20415	- Light	42 35 20 N 87 48 31 W	Iso R 6s	50 15	12	Red conical tower. 50	HORN: 1 blast ev 30s (3s bl). Operates from Apr. to Dec.
		*					17/02
20480	- Reef Light Marks east side of reef.	42 43 39 N 87 44 10 W	FI W 6s	50 15	11	On skeleton tower. 50	HORN: 1 blast ev 15s (2s bl). Operates continuously from Apr. to Nov.
		*			*		17/02

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME VII LIGHT LIST, 2002

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
20616	OAK CREEK PARK LIGHT 2	42 51 59 N 87 50 15 W	FL R 4s	27 8		TR on pile on breakwater.	Private aid.
		*					17/02
20726	Water Institute Lighted Research Buoy						Remove from list.
							*
							17/02
	*Add Heading: *Milwaukee						
*20762	Water Institute Lighted Research Buoy	43 12 33 N 87 39 22 W	Q Y			Yellow.	Private aid.
							17/02
MANITOWOC AND SHEBOYGAN (Chart 14922)							
Sheboygan							
20820	- BREAKWATER LIGHT	43 44 58 N 87 41 34 W	FI W 4s	55 17	9	On cylindrical tower. 50	HORN: 1 blast ev 30s (3s bl). Operates from Apr. to Nov.
		*					17/02
22055.5	Saumico Lighted Buoy 5	44 37 52 N 88 00 18 W	Q G			Green.	Maintained from May 1 to Oct. 31. Private aid.
		*					17/02
22055.7	Saumico Lighted Buoy 7	44 37 48 N 88 00 24 W	Q G			Green.	Maintained from May 1 to Oct. 31. Private aid.
							*
							17/02

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.